

PRODUCTS

PAR FRAME GRADE (BC GRADE) BIRCH FOR FURNITURE & UPHOLSTERY MANUFACTURE

PAR Birch we export to upholstery manufactures and other furniture producers. All production is supplied from our Estonian sawmills.

Main specification is planed (PAR) Frame Grade Birch (BC grade) & sawn Asian grade (AB grade) ; 3 or 4 sides clear (A grade) sawn KD birch on request.

In Frame Grade we offer standard long lengths material & cut-to-length rails to manufacturers, also 2 or 4 eased edged material (S2S or S4S).

Frame grade is suitable for sofa and bedframes production.

Standard specification of Frame Grade (BC grade) PAR Birch:

Thickness: 24mm

Width: 24/ 35/ 46/ 57/ 70/ 95/ 120/ 145mm

Lengths: 500mm to 3200mm



ASIAN GRADE (A and AB grade)

AB grade is suitable for furniture parts/components, as well as for other smaller products which need knot free material.

In AB grade the redheart is not permitted on 3 sides, on 1 side very small redheart is allowed. The distance between the defects/knots has to be at least 50cm and the material has to give clear cuttings at least 70% of the length of the board.

Standard specification of Asian Grade (A grade and AB grade) sawn KD birch:

Thickness: 25 & 50mm (AB grade) ; 25 mm (A grade)

Width: 75/ 100/ 125/ 150mm

Length: 2100mm to 3200mm



PALLET & PACKAGING MATERIAL – MIXED HARDWOOD/SOFTWOOD

We buy pallet material from sawmills in Estonia which allows us to offer specifications to suit our customers requirements. Material is produced from hardwood (aspen/alder/birch) and softwood (spruce/pine) , cut and packaged to length, mainly unseasoned. We can offer also HT 56/30 treated pallet material.

Standard pallet material:

- thickness: 14mm to 100mm
- width: 50mm to 150mm
- length: 500mm to 4200mm



WHITEWOOD & REDWOOD FOR TIMBER & BUILDING MERCHANTS

Construction timber we export according to availability and customer requirement. We can offer Non Graded Unseasoned or Graded C16 Kiln Dried material.

Standard sizes are:

Thickness: 22/ 47/ 75mm

Width: 75/ 100/ 125/ 150/ 175/ 200/ 225/ 250mm

Length: up to 6050 mm

